



## PATENT ABSTRACTS OF JAPAN

(11)Publication number : 07-230073

(43)Date of publication of application : 29.08.1995

(51)Int.Cl.

G02F 1/133

G09G 3/36

(21)Application number : 06-333480

(71)Applicant : SEIKO EPSON CORP

(22)Date of filing : 15.12.1994

(72)Inventor : ITO SATORU

(30)Priority

Priority number : 05325170

Priority date : 22.12.1993


Priority country : JP

(54) LIQUID CRYSTAL DISPLAY SYSTEM AND METHOD OF SUPPLYING POWER SOURCE

(57)Abstract:

PURPOSE: To provide a power supply method optimum for the case when ranges of source voltages applied to a scan driver, a signal driver are different from each other.

CONSTITUTION: A power source supply part 5 supplies source voltage group V11, VC1, V12 of the same polarity provided with a narrow source voltage range to the signal driver 2, and supplies the source voltage group V10, VC2, V15 of the same polarity provided with a wide source voltage range to the scan driver 3. Then, central voltages VC1, VC2 are equal. The power source supply part 5 is provided with a means for adjusting the value of the supplied source voltage. A control signal, etc., from a control part 1 is level changed by a potential change part 6. When display off is realized, the outputs of the signal driver 2, the scan driver 3 are made a VC level. By such a manner, the adjustment of a liquid crystal driving voltage is realized by a simple adjustment means while holding a precise voltage ratio.



## LEGAL STATUS

[Date of request for examination]

31.10.2000

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

3407447

[Date of registration]

14.03.2003

[Number of appeal against examiner's decision]